

Inj.-qty. cm³/
 difference 1000s.: 4.50...12.50
 KSB/AFB
 valve Volt: 12
 Shutoff
 electromagnet Volt: 12
 TD-travel diff.measurement
 correttore anticipo iniezione (SV)
 1.Speed 1/min: 1200
 TD-travel
 difference mm: 0.50...0.70
 KSB/AFB
 valve Volt: 12
 Shutoff
 electromagnet Volt: 12

Inspection-pump test specifications
 Test specifications in parentheses

Timing-device characteristic:

2nd speed 1/min: 2200
 TD travel mm: 9.10...9.90
 mm: (8.80...10.20)
 KSB/AFB
 valve Volt: 12
 Shutoff
 electromagnet Volt: 12
 3rd speed 1/min: 1200
 TD travel mm: 4.30...4.70
 mm: (3.80...5.20)
 KSB/AFB
 valve Volt: 12
 Shutoff
 electromagnet Volt: 12
 4th speed 1/min: 800
 TD travel mm: 1.90...2.70
 mm: (1.60...3.00)
 KSB/AFB
 valve Volt: 12
 Shutoff
 electromagnet Volt: 12
 5th speed 1/min: 600
 TD travel mm: 0.60...1.40
 mm: -
 KSB/AFB
 valve Volt: 12
 Shutoff
 electromagnet Volt: 12
 8th speed 1/min: 1200
 TD travel mm: 3.80...6.20
 mm: (3.80...6.20)
 Shutoff
 electromagnet Volt: 12
 9th speed 1/min: 300
 TD travel mm: 2.70...4.30
 mm: (2.50...4.50)
 Shutoff
 electromagnet Volt: 12
 10th speed 1/min: 800

K15

TD travel mm: 2.80...5.20
 mm: (2.80...5.20)

Shutoff
 electromagnet Volt: 12

Supply-pump pressure characteristic:

1st speed 1/min: 2200
 Supply-pump
 pressure bar: 6.50...7.10
 KSB/AFB
 valve Volt: 12
 Shutoff
 electromagnet Volt: 12
 2nd speed 1/min: 1200
 Supply-pump
 pressure bar: 4.00...4.60
 KSB/AFB
 valve Volt: 12
 Shutoff
 electromagnet Volt: 12
 3rd speed 1/min: 800
 Supply-pump
 pressure bar: 3.00...3.60
 KSB/AFB
 valve Volt: 12
 Shutoff
 electromagnet Volt: 12
 4th speed 1/min: 600
 Supply-pump
 pressure bar: 2.40...3.00
 KSB/AFB
 valve Volt: 12
 Shutoff
 electromagnet Volt: 12

Overflow quantity at overflow valve:

1st speed 1/min: 600
 KSB/AFB
 valve Volt: 12
 Shutoff
 electromagnet Volt: 12
 Overflow : 41.70...83.40
 quantity cm³/10s: (41.70...83.40)
 2nd speed 1/min: 2200
 KSB/AFB
 valve Volt: 12
 Shutoff
 electromagnet Volt: 12
 Overflow : 55.60...139.00
 quantity cm³/10s: (55.60...139.00)

Delivery-quant. and breakaway char.:

2nd speed 1/min: 2700
 KSB/AFB
 valve Volt: 12
 Shutoff