

2nd speed 1/min: 550
KSB/AFB
valve Volt: 12
Shutoff
electromagnet Volt: 12
Del. quantity cm³/: 7.00...10.50
1000S.: -

Load-dependent start of delivery:
Inj.-qty.dif.measurement:

1st speed 1/min: 1500
Inj.-qty. cm³/ : 8.00...16.00#
difference 1000S.: (8.00...16.00)
KSB/AFB
valve Volt: 12
Shutoff
electromagnet Volt: 12
2nd speed 1/min: 1500
Inj.-qty. cm³/: 5.00...7.00*
difference 1000S.: -

TD-travel dif.measurement:
correttore anticipo iniezione (SV):
1st speed 1/min: 1500
TD-travel : 0.80...1.00#
difference mm: (0.80...1.00)
KSB/AFB
valva Volt: 12
Shutoff
electromagnet Volt: 12

SP press.-dif.measurement:
pompa di mandata (FP):
1st speed 1/min: 1500
Supply pump-
pressure : 0.10...0.30*
difference bar: -

Automatic starting fuel delivery:

1st speed 1/min: 220
KSB/AFB
valve Volt: 12
Shutoff
electromagnet Volt: 12
Del. quantity cm³/: 52.00...78.00
1000S.: (52.00...78.00)

2nd speed 1/min: 300
KSB/AFB
valve Volt: 12
Shutoff
electromagnet Volt: 12
Del. quantity cm³/: 35.50...45.50
1000S.: (35.50...45.50)

4th speed 1/min: 100
KSB/AFB
valve Volt: 12

K24

Shutoff
electromagnet Volt: 12
Del. quantity cm³/: 50.00...80.00
1000S.: (50.00...80.00)

Shutoff electromagnet:

Cut-in
min voltage : 10.0
Rated voltage : 12.0

Mounting and assembly dimensions:

Designation
K mm: 3.2...3.4
KF mm: 5.6...6.0
MS mm: 1.0...1.4
LDA stroke mm: 6.2
XK mm: 18.8...20.8
XL mm: 10.0...13.4
Ya mm: 37.2...39.2
Yb mm: 37.5...43.5

Overflow restriction 0.75 mm - Part No.
..343,..344

Operate control lever after each
manifold-pressure compensator pressure
change.

* Correction at adjusting nut (46)