

Shutoff
 electromagnet volt: -
 Idle delivery:
 1st speed 1/min: 425
 Shutoff
 electromagnet Volt: 12
 Del. quantity cm³/: 6.00...8.00
 1000S.: (3.00...11.00)
 Dispersion cm³/: 3.0
 1000S.: (4.0)
 2nd speed 1/min: 500
 Shutoff
 electromagnet Volt: 12
 Del. quantity cm³/: (1) 0.0...6.0
 1000S.: (2) 2.0...10.0

Part-load del. at 3rd inj.-qty.
 terza fermo della portata
 stop (EGR set)
 scarico) (ARF)
 gaz d'échappement-ARF)
 Spacing mm: 20.0

1st speed 1/min: 1250
 Shutoff
 electromagnet Volt: 12
 Del. quantity cm³/: 18.00...19.00
 1000S.: (16.00...21.00)

Automatic starting fuel delivery:

1st speed 1/min: 300
 Shutoff
 electromagnet volt: 12
 Del. quantity cm³/: 40.00...70.00
 1000S.: (40.00...70.00)

2nd speed 1/min: 420
 Shutoff
 electromagnet Volt: 12
 Del. quantity cm³/: 21.00...31.00
 1000S.: (21.00...31.00)

4th speed 1/min: 100
 Shutoff
 electromagnet Volt: 12
 Del. quantity cm³/: 45.00...85.00
 1000S.: (45.00...85.00)

Shutoff electromagnet:

Cut-in
 min voltage : 10.0
 Rated voltage : 12.0

Mounting and assembly dimensions:

Designation

N23

K	mm: 2.7...2.9
KF	mm: K-OT
MS	mm: 1.8
TLA-E	mm: 2.5
Ya	mm: 42.8...45.8
Yb	mm: 60.0...72.0

Remarks:
 :
 :